By 2028, a world-class Army that is a source of national pride.

HEADQUARTERS PHILIPPINE ARMY OFFICE OF THE ARMY QUARTERMASTER Fort Andres Bonifacio, Metro Manila

PHILIPPINE ARMY RUBBER SHOES, BLACK QM SPEC NR IC-21PARSB dtd 05 July 2019

LIST OF REQUIRED PROTOTYPE SAMPLES AND SWATCH MATERIALS FOR TESTING

1. FOR POST QUALIFICATION TEST

PROTOTYPE SAMPLES

RDC - Three (3) pairs, any size but the Three (3) pairs must be of same

OAQM – One (1) pair

sizes

SWATCH MATERIALS (Minimum requirement)

Synthetic Leather	40 cm x 40 cm
Vamp, Quarter, Side Guard, Outside	50 cm x 50 cm
Collar, Back Counter And Tongue	
Tongue Loop Material	1 meter
Tongue Lining and Inside Collar	50 cm x 50 cm
Eyeletstay Reinforcement	40 cm x 40 cm
Toe Cap Reinforcement	50 cm x 50 cm
Insole Material (3 rd layer)	50 cm x 50 cm
Thread for Upper Fitting	10 meters
Thread for Insole Stitching	10 meters

2. FOR ACCEPTANCE TEST

Four (4) pairs – Picked at random from delivery

Colonel, QMS (GSC) P.



